



India's 1st
most
Fuel efficient
TRACTOR RANGE



**INDO FARM
2035 DI DX**



Heavy 1400 Kgs Lift



Oil Immersed Brakes



Straight Rear Axle



Epicyclic Reduction



Dual Clutch

INDO FARM 2035 DI DX

Technical Specifications

	2035 DI	
H.P. Range	38	
Type	Diesel, Four Stroke Direct Injection	
No. of Cylinders	Three	
Bore/Stroke	91.44/127 mm	
Compression Ratio	18.5:1	
Rated Speed	2000 RPM	
Max. Torque Speed	1200-1300 RPM	
Air Cleaner	Oil Bath Type, with Cyclonic Pre-Cleaner	
Fuel Pump	Inline, Make : Bosch India	
Cooling System	Water cooled	
Clutch System	I Single/Double ii) Main Clutch Disc Cerametallic	
Hyd. Pump	Gear Type	
Lifting Capacity	1400 kg at Lower Link Ends	
Electrical	12 Volts-75 Ah-Battery Self Starter Motor & Alternator	
Tyre	Front Rear	6.00 x 16 12.4 x 28
Wheel Track	1355-1895 mm	
Measurement	Length Width Height upto steering	3465 mm 1680 mm 1615 mm
Min. Ground Clearance	400 mm	
Weight	1855 kg	
P.T.O.	1. No. of Splines 2. PTO Speed	6 1000 RPM 6 540 RPM in Dual Clutch
Driver's Seat	Adjustable	
Transmission	No. of Gear Speeds 8 Forward 2 Reverse	
Steering	Mechanical - Recirculating ball type	
Steering wheel dia	430 mm	
Min. Turning radius	3.2 m	
Brake Type	i) Dry: Double disc type (190 mm dia) with parking brake lever ii) Wet : Oil immersed multiple discs (Optional)	

Hydraulic (ADDC) : Two lever, automatic Draft and Position control with mix control.

1. Position Control : To pre-select and automatically maintain certain position or depth of the implement attached to three-point-linkage.
2. Draft Control : To automatically raise and lower an attached implement as the draft or resistance of the implement increases or decreases.
3. Mix Control : To automatically maintain shallow depths in loose soils where draft control is inefficient.

Gear Speed (12.4 x 28 Rear Tyre)			
Direction	Gear	Road Speed (km/h)	
		Low	High
Forward	1	2.32	9.12
	2	3.60	14.16
	3	5.36	21.08
	4	7.12	28.00
Reverse	1	2.90	11.40

Suitable Implements

- 9 Tine Tiller
- 2 Bottom M.B. Plough
- 12 Disk Harrow
- 4 Ton Trailer
- Rotavator 36 blades


Accessories with Every Tractor

- Trailer Hook
- Draw bar
- Fender Guard
- Heavy Bumper
- Tool Kit
- Operator Manual


All the above specifications are subject to change without notice.
For detailed information contact your nearest dealer.

Authorised Dealer


SPECIAL FEATURES



8+2 Speed Gear Box.
Speeds available for all applications.




Brakes on Intermediate shafts
resulting in no water ingress
during puddling.




High displacement,
Powerful Engine.




Recirculating Ball type
Steering prevents transmission of
shocks to the steering wheel.




Straight Rear Axle for easy
maintenance and minimum
wear & tear.



Low maximum rated Engine
RPM - higher Engine life
due to low wear and tear.



Epicyclic Reduction for
High/Low Speeds-reduces
noise & increases life.



Oil immersed Brakes for better
braking due to larger braking area
& longer life due to oil cooling.

INDO FARM
EQUIPMENT LIMITED
An ISO 9001:2008 Certified Company

Export Promotion Industrial Park, Phase-II, Baddi-173 205, Distt. Solan, H.P.
Tel. : (+91)-1795-274241 (8 Lines); Fax : (+91)-1795-274308-309
Email : mail@indofarm.in; Website : www.indofarm.in

