INDO FARM

POWER+MILEAGE

India 1st Most

POWER+MILEAGE

Tractor Range

INDO FARM 3055 NV C-MESH

4WD

Power Steering

Heavy 1800 Kgs Lift

Oil Immersed Brakes

Heavy Duty Front Axle

Reverse PTO

DC Valve

Dual Clutch

Dry Air Cleaner

INDO FARM 3055 NV C-MESH (2WD/4WD)

Technical Specifications

		2WD	4WD
H.P. Range		55	
Type		Diesel, Four Stroke Direct Injection	
No. of Cylinders		Three	
Bore/Stroke		105/110 mm	
Rated Speed		2200 RPM	
Air Cleaner		Dry Type	
Fuel Pump		Inline, Make : Bosch India	
Cooling System		Water cooled	
Clutch System		i) Dual ii) Main Clutch Disc Cerametallic	
Hyd. Pump		Gear Type	
Lifting Capacity		1800 kg at Lower Link Ends	
Electrical		12 Volts-75 Ah-Battery Self Starter Motor & Alternator	
Tyre 18	Front	7.50 x 16	8.00 x
	Rear	14.9 x 28	14.9 x 28
Wheel Track		1355-1940 mm	1310-1940 mm
Measurement	Length	3700 mm	3760 mm
	Width	1850 mm	
	Height upto steering	1680 mm	
	Min. Ground Clearance	420 mm below RT Housing	380 mm below RT Housing
Min. Turning radius		3.5 m	4.0 m
Weight		2260 kg	2370 kg
P.T.O. 1. No. of Splines 2. PTO Speed		 6 540 RPM	
Driver's Seat		Adjustable	
Transmission No. of Gear Speeds		 8 Forward 2 Reverse	
Steering		Power Steering	
Steering wheel dia		380 mm	
Brake Type		i) Wet : Oil Immersed Multiple disc ii) Dry : Dry double disc (Optional)	
Actuation		Mechanical, independent right/left or combined	
Parking		Through hand lever, by locking brake pedals	

Hydraulic (ADDC) : Two lever, automatic Draft and Position control with mix control.

1. Position Control : To pre-select and automatically maintain certain position or depth of the implement attached to three-point-linkage.
2. Draft Control : To automatically raise and lower an attached implement as the draft or resistance of the implement increases or decreases.
3. Mix Control : To automatically maintain shallow depths in loose soils where draft control is inefficient.

Gear Speed (14.9 x 28 Rear Tyre)			
Direction	**Gear**	**Road Speed (km/h)**	
		Low	**High**
Forward	1	2.69	10.79
	2	3.83	15.37
	3	6.06	24.24
	4	8.21	32.93
Reverse	1	3.57	14.32

Suitable Implements
11 Tine Tiller
3 Bottom M.B. Plough
14 Disk Harrow
5 Ton Trailor
Rotavator 42 blades

Accessories with Every Tractor

- Trailor Hook
- Draw bar
- Fender Guard
- Heavy Bumper
- Tool Kit
- Operator Manual

All the above specifications are subject to change without notice. For detailed information contact your nearest dealer.

Authorised Dealer

SPECIAL FEATURES

Constant Mesh Gear Box with Side shift gear levers for easy gear shifting & more leg space.

Straight Rear Axle, Less maintenance and repair



Heavy Duty Front Axle (2WD)/ Power Steering



Heavy Duty Front Axle (4WD)/ Power Steering



Heavy 1800 kgs Lift, suitable for heavy implements and tipping trailers with higher loads

Use to lift the trolley without lifting of hydraulic lift.



Oil immersed Brakes for better braking due to larger braking area & longer life due to oil cooling.

Dry Air Cleaner

INDO FARM EQUIPMENT LIMITED

An ISO 9001:2008 Certified Company

ISO 9001-2008 Registered

IN-001 Accrediting Certifying Bodies - Australia

Export Promotion Industrial Park, Phase-II, Baddi-173 205, Distt. Solan, H.P.
Tel. : (+91)-1795-274241 (8 Lines); **Fax :** (+91)-1795-274308-309
Email : mail@indofarm.in; **Website :** www.indofarm.in